

High Resolution VF Dome Camera with OSD



Main Features

- ⇒ 1/3" SONY Super HAD II CCD
- ⇒ 540 TVL High Resolution Camera
- ⇒ 0 LUX/F1.2(IR ON)
- ⇒ 4-9mm Vari Focal auto iris Lens
- ⇒ OSD, D-WDR, DNR, Motion Decton, Privacy Masking, Mrror, AWB, AGC, BLC
- ⇒ CE, FCC and RoHS Certified



| Feature | Specification |
|-------------------------|--|
| Image Sensor | 1/3" SONY Super HAD II CCD |
| Pixels | PAL:500 (H)x582(V) |
| Resolution | 540 TVL |
| Min. Illumination | 0.1 LUX/F1.2 |
| S/N Ratio | more than 48 dB(AGC OFF) |
| Electronic Shutter | 1/50(60)sec-1/100,000sec |
| Lens | 4-9mm Vari Focal auto iris Lens |
| Gamma Correction | 0.45 |
| White Balance (AWB) | ATW1 / ATW2 / MANUAL / AWC->SET / ANTI.CRL |
| Gain Control (AGC) | OFF /LOW / MID / HIGH |
| Back Light Compensation | BLC / HBLC / OFF |
| WDR | ON/OFF |
| Sync | Internal Sync |
| Video Output | Composite 1.0V P-P/75Ω |
| Special Functions | OSD, D-WDR, DNR, Motion Decton, Privacy Masking, Mrror |
| Power Supply | DC12V±10% |
| Power Consumption | <2W |
| Dimensions | 128(R)×90(H)mm |
| Weight | 480g |
| Operating Temperature | -10°C ~ 50°C/30%~80%RH |
| Certifications | CE & FCC |