

CP-DY70M-E

Super High Resolution Dome Camera with OSD



Main Features

- 1 / 3" SUPER HAD II Hi-sensitive CCD & DSP
- 700 TVL Super High Resolution Camera
- 0.01 lux @ F1.2
- 3.6 mm Fixed Lens
- AGC, AES, BLC, Mirror, Privacy Masking and Motion Detection
- D-WDR, 2D-DNR
- CE, FCC and RoHS Certified



Specifications

| | |
|-------------------------|---|
| Image Sensor | 1 / 3" Sony SUPER HAD II Hi-sensitive CCD & DSP |
| Pixels | PAL:960Hx582V, NTSC:967Hx494V |
| Resolution | 700 TVL |
| Min. Illumination | 0.01 lux @F1.2 |
| S/N Ratio | more than 50dB |
| Electronic Shutter | 1/50(1/60) - 1/100000 Sec |
| Lens | 3.6 mm |
| Gamma | 0.45 |
| White Balance (AWB) | ON/OFF Selectable |
| Gain Control (AGC) | ON/OFF Selectable |
| Back Light Compensation | ON/OFF Selectable |
| Sync | Internal |
| Video Output | 1.0 Vp-p/75 ohm |
| Special Functions | OSD, Camera Title, Mirror, Privacy Masking=8, Motion Detection=4, D-WDR, 2D-DNR |
| Power Supply | DC 12V ± 5% |
| Power Consumption | <3W |
| Dimensions | 95 x 130 |
| Weight | 300 gms |
| Operating Temperature | -20~50 °C |
| Certifications | CE, FCC, RoHS |