

CP-ND10/20-R

Full HD Mini Dome IP Camera



Main Features

- Progressive Scan CMOS Sensor
- Full HD 1080p @15fps / HD 720p real-time at dual streaming
- H.264 and MJPEG compression
- Power over Ethernet (802.3af)
- Motion Detection
- Privacy Masks
- Security Torx against tampering

Specifications	CP-ND10-R	CP-ND20-R
Image Sensor	1/2.7" Progressive CMOS	
Minimum Illumination	0.1 lux @ F 1.5	
Shutter Speed	1 ~ 1/10000 sec.	
White Balance	Manual / AWB / ATW	
Lens	4.0 mm	
Video Compression	H.264/MJPEG	
Video Streaming	H.264 + MJPEG/H.264 + H.264	Simultaneous H.264 + H.264
Resolution	H.264 : Full HD 1080p/SXGA/HD 720p/D1/VGA/CIF/QVGA, MJPEG : Full HD	
Frame Rate	HD 25/30 fps, Full HD 15 fps	HD 25/30 fps, Full HD 25 fps
Digital Zoom	Support	
Motion detection	On/Off	
Privacy Mask	Support	
Privacy Mask Type	Transparent, Color	
Tampering Alarm	On/Off	
Audio	Mic in	
Audio Compression	G.711 / G.726	
Event Notification	HTTP, FTP, SMTP	
Multiple Languages	English, French, German, Italian, Korean, Simplified Chinese, Russian	
Interface	10/100Mbps Ethernet (RJ-45)	
Protocol	IPv4/v6, TCP/IP, UDP, RTP, RTSP, HTTP, HTTPS, ICMP, FTP, SMTP, DHCP, PPPoE, UPnP, IGMP,	
Password Levels	User and Administrator	
Security	HTTPS, IP Filter, IEEE 802.1X	
Internet Browser	Internet Explorer (6.0+), Chrome, Firefox, Safari	
User Account	20	
Micro SD	SDHC support	
Operating Temperature	10° ~ 50°C (14° ~ 122° F)	
Humidity	10% to 90%, No Condensation	
Power Source	PoE	
Power Consumption	3.8W	
Weatherproof Standard	IP66	
Regulatory	CE, FCC, RoHS Compliant	
Dimension	Ø117 x 50 mm (4.6 x 2.0 inches)	
Weight	180 g (0.40 lbs)	