

KPC139D

35 IR LEDs Camera



● FEATURES

- (1) High sensitivity in the dark environment, 0.05 Lux / F2.0, 0 Lux (IR ON)
- (2) Day and night features for 24-hour surveillance
- (3) Excellent image quality
- (4) IR LED effective range reaches up to 25 meters
- (5) IP67, suitable for outdoor use

● SPECIFICATIONS*

MODEL	KPC139D
Pick-up Element	1/3" Color CCD image sensor
Number of Pixels	512(H)X492(V) <NTSC> / 512(H) x 582(V) <PAL>
Resolution	Standard
Min. Illumination	0.05 Lux / F2.0, 0Lux (IR ON)
IR LED	35 units
IR Effective Range	25 Meters
S/N Ratio	More than 48dB (AGC off)
Electronic Shutter	1/60 (1/50) to 1/100,000 sec.
Lens	f3.6mm / F2.0
Lens Angle	92.6°
White Balance	ATW
AGC	Auto
IRIS Mode	AES
IP Rating	IP67
Video Output	1.0 Vp-p composite, 75Ω
Operating Temperature	0°C~40°C
Power Source (±10%)	DC12V
Current Consumption (±10%)	70mA (IR OFF), 390mA (IR ON)
Gross Weight (g)	430
Dimensions (mm)**	142(H) x 75 (Φ)

* The specifications are subject to change without notice.

** Dimensional Tolerance: ± 5mm