CP-DY70ML2-E

Super High Resolution IR Dome Camera with OSD - 20 Mtr

Main Features

- 1 / 3" Super HAD II Hi-sensitive CCD & DSP
- 700 TVL Super High Resolution Camera
- 0 lux @ F1.2 (IR ON)
- 3.6 mm Fixed Lens
- IR Range of 20 Mtrs with 24 LED's
- AGC, AES, BLC, Mirror, Privacy Masking and Motion Detection
- D-WDR, 2D-DNR
- CE, FCC and RoHS Certified

Specifications

Image Sensor	1 / 3" Sony Super HAD II Hi-sensitive CCD & DSP
Pixels	PAL:960Hx582V, NTSC:967Hx494V
Resolution	700 TVL
Min. Illumination	0 lux @F1.2
S/N Ratio	more than 50dB
Electronic Shutter	1/50(1/60) - 1/100000 Sec
Lens	3.6 mm
Gamma	0.45
White Balance (AWB)	ON/OFF Selectable
Gain Control (AGC)	ON/OFF Selectable
Back Light Compensation	ON/OFF Selectable
IR	24 LEDs, Upto 20 Mtrs
Sync	Internal
Video Output	1.0 Vp-p/75 ohm
Special Functions	OSD, Camera Title, Mirror, Privacy Masking=8, Motion Detection=4, D-WDR, 2D-DNR
Power Supply	DC 12V ± 5%
Power Consumption	<5W
Dimensions	75 x 110
Weight	440 gms
Operating Temperature	-20~50 °C
Certifications	CE, FCC, RoHs