

CP-SY37C-ET

Day & Night 37x Optical Zoom Speed Dome camera



Main Features

- 1/4" SONY Super HAD CCD
- 37 X optical zoom and 12X digital zoom
- Day/Night + ICR, High resolution of 540 TV Line (Color)
- 360° continuous pan rotation, 90° tilt rotation, auto flip
- Manual speed 0.01°~500°/S, Preset speed 500°/S
- Pan 0.01°~180° /S, Tilt 0.01°~120° /S, Preset: 500° /S
- Programmable 220 preset positions
- 4 pattern tours, each one 180s memory
- 8 cruising tracks, each cruising track has 32 preset positions
- 6 alarm inputs and 2 outputs
- 8 privacy zones
- RS-485 multiple protocols, Pelco_P, Pelco_D compatible
- IP66-rated waterproof
- Build-in fan and heater, temperature auto control.
- Outdoor wall mount housing

Specifications

Image Sensor	1/4" SONY Super HAD CCD
Resolution	540TVL
S/N Ratio	more than 52dB
Electronic Shutter	1/50 ~ 1/90,000
Iris Control	DC Auto
Zoom Optical	37X
Zoom Digital	12x
Lens	3.5mm-129.5mm
Focus Mode	Auto/Manual
White Balance (AWB)	Auto / Manual (1800°K ~ 10,500°K)
Gain Control (AGC)	LOW / MEDIUM / HIGH / OFF
Day & Night (ICR)	Yes
Special Functions	OSD, Auto Cruise, Auto Scan
Pan Range	360° continuous
Pan Speed	0.01°~180° /S
Tilt Range	90°(Auto Flip)
Tilt Speed	0.01°~120° /S
Proportional Pan/Tilt Control	Yes
Number of Presets	220
Preset Speed	500°/s
Surge Protection	Yes
Alarm	6 alarm inputs and 2 outputs
Fan & Heater	Yes
Communication	RS-485
Sync. System	Internal synchronization
Video Output	1Vp-p75ohm
Power Supply	AC24V±10%
Power Consumption	Indoor : 10W Outdoor : 25W
IP Rating	IPIP 66
Operating Temp	Indoor : (0°C~+50°C) Outdoor: (-35°C~55°C)
Certifications	CE & FCC