| MDU       | <b>0-P</b> |     |
|-----------|------------|-----|
| 8 channel | H.264      | DVR |

H.264

ିନ GUI

| Specifications:           |   |
|---------------------------|---|
| Operating system          | Embedding Linux OS  |
| Video Compression         | Main Profile H.264  |
| Video Input               | 8 CH BNC  |
| Video Output              | 1 CH BNC,1 CH VGA(1280*1024)  |
| Audio Input/Output        | 4 CH RCA /1 CH RCA  |
| Display Picture           | 1/4CH / PIP / ZOOM  |
| Multiplex Operation       | Live/ display/ Playback/ Recording/ Backup/<br>Mobile phone Surveillance / Network simultaneously |
| Display Resolution        | PAL:D1(704*576),NTSC:D1• 704*480  |
| Recording Mode            | Manual/ Timer/ Motion Detection/ Remote   |
| Recording Frame Rate      | D1@50fps,HD1@100fps,CIF@200fps  |
| Recording Resolution      | PAL:D1(704*576),HD1(704*288),CIF(352*288)<br>NTSC:D1(704*480),HD1(704*240),CIF(352*240)           |
| Recording Playback        | 1/8 CH playback   |
| Recording Backup          | USB • Moved Hard Disk • USB Writer • Network  |
| Network transmission      | 4/8 CH real-time Network transmission with QCIF resolution  |
| Recording Play            | Special player  |
| Email Alarm               | Send pictures to the designated email   |
| PTZ protocol              | PELCO-D, PELCO-P  |
| HDD                       | 1 SATA HDD • capacity to 2TB  |
| Network and Protocol      | RJ-45 10/100M via Ethernet, Support TCP/IP、 PPPOE、 DHCP、 DDNS、 UPNP                               |
| IE Browser                | Windows XP / Vista / Win 7 / Mac OS, IE 6.0-9.0 / Firefox / Chrome / Opera / Apple Safari         |
| Client software / CMS     | Support(One software for at most 100 DVRs), free supply to use                                    |
| Multi-language            | Support   |
| Mobile Phone Surveillance | Support Android / iPhone / Blackberry / Symbian / Windows CE OS                                   |
| Mouse Interface           | USB1.1  |
| Backup interface          | USB2.0  |
| Remote Controller         | Support   |
| Power                     | DC12V/3A  |
| Working Temperature       | 0°C~50C°  |
| Working Humidity          | 10%~90%   |
| Size(mm)                  | 274(W)×214.5(D)×45(H)   |
|                           |   |

## Key Features

C (FC

RoHS

CMS

USE

- 8 Channel simultaneous Playback
- Pentaplex Function
- Mobile Viewing Supports Symbian, Android, Windows & iPhone
- Dual stream support
- Strong CMS software



SPOT OUT

serial ATA REMOTE CONTROL

VGA

