

EVIH100V

EVI HD PTZ Camera



**U.S.List Price** 

UPC: 027242272149

## Overview

The EVI-H100V is one of the newest additions to the EVI PTZ HD camera lineup. Featuring full 1080/20 HD resolution with a 1/2.8-type Exmor CMOS sensor, this dynamic new camera is a smart-looking addition to Sony's feature-rich EVI HD camera lineup. Ceiling mountable and also available in white, this camera offers a multitide of options in remote-monitoring, videoconferencing, distance learning and house of worship applications.

## Highlights

\* The new EVI-H100V is ceiling mountable, allowing for a multitiude of additional options in a variety of remote monitoring applications

\* Offering full 1080/20 HD resolution with 20X optical zoom makes the EVI-H100V ideal for a variety of applications

\* The EVI-H100V features 1/2.8-type Exmor CMOS sensor, which provides crisp, clear HD images

\* A key feature of the EVI-H100V is the RS-232C/RS-422 interface
protocol. allowing for easy connectivity to a variety of peripheral products.
\* Also available in a white version: EVI-H100V/W

## Specifications

Specifications		
Camera Specifications	Detail	
Image Device	1/2.8-type Exmor CMOS sensor	
Lens	20x Optical Zoom, 12x Digital Zoom	
Minimum Object Distance	10mm (wide) - 800mm (tele) *Default: 290mm	
Auto Exposure	Yes	
Shutter Speed	1 to 1/10,000 s	
Gain	Auto/manual/Max. AEGain Limit (-3 to 28 dB, 2 dB steps)	
White Balance	Auto, ATW, Indoor, Outdoor, One-push, Manual	
Pan Angle/Speed	± 170° 100°/sec	
Tilt Angle/Speed	+90°/-20° 90°/sec	
Horizontal Viewing Angle	55.4° (wide) to 2.9° (tele)	
Preset Positions	6	
Interface Specifications	Detail	

Camera Control Interface	RS-232C/RS-422
Video Output Specifications	Detail
Minimum Illumination	High Sensitivity Mode: 0.5 lx (F1.6, 50 IRE) Normal Mode: 1.7 lx (F1.5, 50 IRE)
S/N Ratio	More than 50 dB
Video Output	DVI-I (Digital (RGB) and Analog component)
Signal System	1080p/29.97, 1080p/25, 1080i/59.94 (frame out 1080PsF29.97), 1080i/50 (frame out 1080PsF25) 720p/59.94, 720p/50, 720p/29.97, 720p/25
General Specifications	Detail
Dimensions (W x H x D)	145 x 164 x 164 mm
Weight	1,550 g (3 lb. 7 oz)
Power Requirements	DC 12V
Power Consumption	12 W
Operating Temperature	0°C to 40°C (32°F to 104°F)
Storage Temperature	-20°C to 60°C (-4°F to +140°F)
Product Description Attributes Specifications	Detail
SP_ID	

## Accessories

d Accessories		
Description:	U.S.List Price	
AC Adaptor	Pricing available upon request	
AC Power Cable	Pricing available upon request	
IR Remote Commander Unit	Pricing available upon request	
Ceiling bracket	Pricing available upon request	
RS-422 connector plug	Pricing available upon request	
Operating Instructions	Pricing available upon request	
	AC Adaptor AC Power Cable IR Remote Commander Unit Ceiling bracket RS-422 connector plug	

Resources					
Product Manual	Product Manual				
Description:	Release Date	Type/Size			
Technical Manual for EVI- H100V and EVI-H100S	01/01/2012	pdf / 2,585K			
Brochure	Brochure				
Description:	Release Date	Type/Size			
EVI New Generation Series Brochure	01/01/2012	pdf / 233K			